



| | | | | | | |
|------------|---------------------|----------|----------------------------|--------------------------|----------------|--------------------|
| Inner beam | Item | A0261665 | Suspension | SAP 100/2865317 | Drawling angle | h=290 |
| Extensions | --- | --- | Angle | SAP 9622 11030 | Side rail | K08-u 140 |
| 500 | Chassis | A0011680 | Roller/roller | +105/-75 (incl. bump BS) | Stake pockets | SE-65-6 2x 10 pcs. |
| 1000 | Inner beam | A0000670 | Type | Coaxtype 240/70 R17.5 | Deck | 28mm Hardwood |
| 1685 | Center beam | --- | Tires (steel load) | 18.000 kg | Spindles | h=1320 |
| 2000 | Outer beam | A0011660 | Single load | 10.000 kg | Draw holes | T15 |
| 2500 | Rear adapter | --- | Landing gear | --- | Type vehicle | 140u-2B |
| 3000 | Beam above axle | A0037070 | Client | COMPONET BROSCHUS B.V. | | |
| 3685 | Steering | H=10624 | Client | BROSCHUS B.V. | | |
| 4000 | Rear | H=10163 | Specification modification | ECh 07009 | | |
| 4375 | Toolbox | --- | Dimensions in mm | Projection | | |
| 4750 | Score sheet carrier | --- | Date | Date | | |
| | Outriggers | --- | Order no. | Order no. | | |
| | | | Preceded 02232 | Tolerances ISO 2768-CL | | |
| | | | | Drawing no. Checked | | |
| | | | | STAND64/1 | | |

SINGLE AXLE SINGLE EXTENDIBLE LOW LOADER